

SPRING BALANCER

*TIGON Spring Balancer Improves Work Safety & Efficiency.
Capacities ranging from 0.5~70kg.*

TIGON



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-00	0.5~1.5	0.5	0.2
TW-0	0.5~1.5	1.0	0.5
TW-3	1.0~3.0	1.3	1.4
TW-5	2.5~5.0	1.3	1.5
TW-9	4.5~9.0	1.3	3.4
TW-15	9.0~15.0	1.3	3.8
TW-22	15.0~22.0	1.5	7.2
TW-30	22.0~30.0	1.5	7.6
TW-40	30.0~40.0	1.5	9.8
TW-50	40.0~50.0	1.5	10.4
TW-60	50.0~60.0	1.5	11.6
TW-70	60.0~70.0	1.5	11.8

HOSE REEL BALANCER SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)	Hose DIA (φ mm)
HW-0	0.5~1.5	1.3	1.6	φ 6.5 / φ 10
HW-3	1.5~3.0	1.3	1.7	φ 6.5 / φ 10
HW-5	3.0~5.0	1.3	1.8	φ 6.5 / φ 10

- Functions both as balancer and hose reel

RETRACTOR SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
RW-0	0.5~1.5	2.0	0.5
RW-3	1.0~3.0	2.0	0.7
RW-5	2.5~5.0	2.0	0.9

- Tension easily adjustable using knob

MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-1R	0.5~1.5	1.5	0.3

- Tension easily adjustable using knob



★ Specifications and designs are subject to change at any time without notice.



Head Office
9-4, Nakaikagami 2-chome,
Ohta-ku, Tokyo 146-8555 Japan
Phone : +81-3-3755-1111 Fax : +81-3-3753-8791

► URL : www.nitto-kohki.co.jp/e ► E-mail : overseas@nitto-kohki.co.jp

Manufactured by
NITTO KOHKI-MIJIN CO.,LTD.



In printing this catalog, the aluminum printing plate was reused, this action avoided generating waste aluminum plate, and contributed to reducing CO2 emissions by 0.00kg.
Smart Energy Co., Ltd. examined this numerical value and confirmed it.
NITTO KOHKI CO., LTD. participates in an Indonesian reforestation project with print by MCP.



DISTRIBUTED BY