



KDA03EVF

**KODIAK BLAST CHILLER
3 TRAYS 600X400 - GN 1/1
DIGITAL DISPLAY**



FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	ELECTRIC
Number of evaporator motors	1
Evaporator Motor speeds	1
Number of condenser motors	1
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC (optional)
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 3/85
Max tray load	4kg

DIMENSIONS

Blast chiller size with handle WxDxH (mm)	760 x 670 x 895
Chamber gross volume (L)	101 L
Chamber usefull volume (L)	91 L
Unit weight (Kg)	77 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	810 x 740 x 1080
Unit weight with packaging (Kg)	92 kg



ELECTRICAL DATA

Compressor 220-230V 1N~2 50/60Hz

Power	0,83kW/0,972kW
Frequency	50/60Hz
Power supply	220-230V 1N~
Amperage	4,9A/5,12
Power cord req.	3G1,5

REFRIGERATION CIRCUIT

Cooling capacity**	1125W (50Hz) 1316W (60Hz)
Cooling capacity per cycle (+90°C > +3°C)	10 kg
Freezing capacity per cycle (+90°C > -18°C)	6 kg
Refrigerant	R452a
Refrigerant load	0,5 kg
Evaporator	Anti-corrosion coating
Climate class	5 (43°C)
Defrost	Evaporator Fan
CO2 equivalent	1,96 Tons

FUNCTIONS

Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanitification	Not available
Ice cream	Not available
Recipes	Not available
Thowing	Not available

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

**Evap-10°, Cond. 45



ACCESSORIES

Stacking kit (SQUERO)	SK46
Stacking kit (SAN GIORGIO SAN MARCO)	SK16
Heated core probe	Optional
Pvoting wheel kit h80	R80
Pvoting wheel kit h100	R100
Ice cream kit	IX13

