



KDA05EVF

**KODIAK BLAST CHILLER
5 TRAYS 600X400 - GN 1/1
DIGITAL DISPLAY**



FUNCTIONAL CHARACTERISTICS

Display	Digital
Supply	ELECTRIC
Number of evaporator motors	1
Evaporator Motor speeds	1
Number of condenser motors	2
Condenser Motor speeds	1
Min chamber temperature (°C)	-35 °C
Core probe	PTC
Chamber material	Fingerprint free co-laminated steel
Frame material	Fingerprint free co-laminated steel
Opening door	Right handle
Door gasket	Magnetic removable
Door frame	Heated inspectable
Insulation	CFC-HFC free HD Poliurethane 60mm

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Wire PA-BIV 5/68
Max tray load	4 kg

DIMENSIONS

Blast chiller size with handle WxDxH (mm)	760 x 670 x 895
Chamber gross volume (L)	101 L
Chamber usefull volume (L)	91 L
Unit weight (Kg)	82 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	810 x 740 x 1080
Unit weight with packaging (Kg)	97 kg



ELECTRICAL DATA

Compressor 220-230V 1N~

Power	1300kW/1500W
Frequency	50/60Hz
Power supply	220-230V 1N~
Amperage	7A
Power cord req.	3G1,5

Compressor 200-208V 1N~

Power	1300kW/1500W
Frequency	50/60Hz
Power supply	200-208V 1N~
Amperage	7,8A
Power cord req.	3G1,5

REFRIGERATION CIRCUIT

Cooling capacity**	1870W (50Hz) 2350W (60Hz)
Cooling capacity per cycle (+90°C > +3°C)	20 kg
Freezing capacity per cycle (+90°C > -18°C)	13 kg
Refrigerant	R452a
Refrigerant load	0,5kg
Evaporator	Anti-corrosion coating
Climate class	5 (43°C)
Defrost	Evaporator Fan
CO2 equivalent	2,55 Tons

FUNCTIONS

Blast chilling cycles	Soft / hard
Deep Freezing	Soft / hard
Temperature regulation	Core probe / Time
Storage	+3°C/-18° automatic
Fish sanification	Standard
Ice cream	Standard
Recipes	Standard
Thowing	Optional

**Evap-10°, Cond. 45



CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Stacking kit (SQUERO)	SK43
Stacking kit (SAN GIORGIO SAN MARCO)	SK44
Heated core probe	Optional
Pivoting wheel kit h80	R80
Pivoting wheel kit h100	R100
Ice cream kit	IX13

